



60 M ANCHOR HANDLING TUG SUPPLY VESSEL-FIFI I BHP 5220 BOLLARD PULL 65 TONNE

PRINCIPAL PARTICULARS

Length Over All	: 60.10 m
Length W.L	: 58.74 m
Breadth Molded	: 16.00 m
Depth Molded	: 5.50 m
Draft Moulded (Design)	: 4.20 m
Draft Moulded (Max)	: 4.85 m
Class	: Bureau Veritas
Flag	: Malaysian / Port Kelang
Built	: 2009
Official No.	: 334053
IMO No.	: 9545259
Call Sign	: 9MIL6
MMSI No.	: 533000481
Hull No.	: 20071
GRT / NRT	: 1669 / 500 MT
Place of Built	: Muhibbah Marine Engineering

PERFORMANCE

Performance Speed	: 13 knots
Economical Speed	: 11 knots
Endurance	: 22 days

CARGO CAPACITIES

Deck Cargo	: 600 mt
Deck Strenght	: 7 mt/m2
Cargo Deck Area	: 390 m2
Potable Water	: 550 m3
Fuel Oil	: 522 m3
Drill Water / SWB	: 550 m3
Foam & Detergent Tank	: 10 m3 each
Dry Bulk Tank	: 170 m3
Liquid Mud Tank	: 177 m3
Base Oil / Brine	: 159 m3

DISCHARGE RATES

Fuel Oil	: 100 m3/Hr @ 90m H
Portable Water / Drill	: 100 m3/Hr @ 90m H
Base Oil	: 1 x 100 m3 / Hr @ 90 m H
Liquid Mud	: 2 x 90 m3 / Hr @ 90 m H 150hp x 2900 rpm for S.G 2.0
Bulk Cement	: 13.0 m3/min, working pressure 5.6 bar
Fresh Water Msker	: 5.5 m3 / 24 hrs (240 lit/hr)

PROPULSION SYSTEM

Main Engines	: 2 x 2610 Bhp @ 750 rpm Yanmar 6EY26
Auxiliary Engines	: Caterpillar 3406C DITA, 2 x 245 Ekw x 415V x 3ph x 1500 rpm
Shaft Alternator	: Leroy Somer, 2 x LSA M50. 154- 4P, 700 kW 50 Hz
Bow Thruster (Electric motor driven)	: 1 x HRP 4008 TT CP 8 mt thrust, 515 kW, 1800 rpm
Propellers	: 2 x CPP in fixed nozzle, Berg BCP 690
Gear Box	: Reintjes, LAF 2346 K41
Steering Gear	: Wagner / Nufoss Steering System, WIN LA2 4.4-45-CB2
Emergency Generator	: 1 x Caterpillar, 86EKW, 415 V, 3 ph, 50 Hz @ 1500 rpm

TOWING/ANCHOR HANDLING EQUIPMENT

Bollard Pull	: 65T
Towing Winch	: Double drums waterfall type, 200mt stall pull x 1000m x 52mm wire rope
Stern Roller	: 1.8m dia x 3.5m length 200 tons SWL
Karm Fork	: 1 set Karmoy Ref.: M330120 SWL 300 tons
Towing Pins	: 1 sets, Zicom, SWL 180 mt
Storage Reel	: 1 x 5 ton @ 0-20m / min

DECK EQUIPMENTS

Capstan	: 2 x 6T @ 0-24m / min
Tugger Winch	: 2 x 10T @ 0-15m / min
Deck Crane	: Type ATB 58/8 @ 5m
Anchor Windlass	: 10T @ 0-12m / min max duty, 40mm chain
Anchor	: 2 x 1590kg Stockless bower anchor

ACCOMMODATIONS

Complement	: 28 men
All cabins fully air-conditioned	
Walk-in Freezer Space	: 10.0 m3
Walk-in Chiller	: 12.0 m3

RADIO & NAVIGATION EQUIPMENTS

SSB	: 1 x Furuno FS-1570, 150W MF / HF
VHF	: 2 x JRC JHS-770S
Radar	: JRC, JMA-5312-6 & 5210-6
Echo Sounder	: JRC JFE-380
Gyro Compass	: Yokogawa CMZ-700B M
GMDSS	: Area 3
Magnetic Compass	: 1 x Lilley & Gillie MK2000
Speed Log	: 1 x JRC, JLN-250
Auto Pilot	: 1 x Navitron PID, NT991G MKII
Navtex Receiver	: JRC NCR-333
GPS Navigator	: 2 x JRC, NWZ-4570
Joystick	: 1 x Intergrated Joystick Control
EPIRB	: 1 set GME, MT 403FF
AIS	: 1 x JRC, JHS-182
Fleet Broadband	: 1 set Thrane & Thrane FB 250
Fax	: 1 set

FIRE FIGHTING EQUIPMENTS (FIFI Class I)

External	
Fire Pump	: Kvaerner, 2 x 1500 m3/hr, main engine driven
Fire Monitor	: 2 monitors (water & form, manual remote control)
Oil Dispersant Boom	: Fitted

Internal

Emergency Fire Pump	: 1 x 40 m3/hr @ 60mH, 15 kW Bombass Azcue BA VM-50/26
---------------------	---

LIFE SAVING & H.S.E. EQUIPMENTS

Search Lights	: 2 x 2000W halogen
Floodlights	: 6 x 1000W halogen : 2 x 500W halogen
Life Jackets	: 28 + 6 spare jackets
Liferafts	: 4 x 15 men capacity
Lifebuoys	: 9 pcs SOLAS approved
Fireman Suits	: As per SOLAS requirement
Immersion Suits	: As per SOLAS requirement
Scrambling Net	: 2 pcs
Rescue Boat	: semi-rigid "Narwhal" 6 person @ c/w 30 hp Outboard Motor : As per SOLAS requirement
Slewing Davit	

AUXILIARY MACHINERIES

G.S and Fire Pump	: 1 x 60 m3/hr @ 60 mH, 18.5 kW, Bombass Azcue BA WM-EP
Bilge and Ballast Pump	: 1 x 60 m3/hr @ 60 mH, 18.5 kW, Bombass Azcue BA WM-EP
Lub Oil Purifier	: 2 x 800 l/hr, Mitsubishi Kaisha, model SJ10G, self-cleaning
Fuel Oil Purifier	: 1 x 1250 l/hr, Mitsubishi Kaisha, model SJ1-G, self cleaning
Sewage Treatment Plant	: DVZ FSU-1000, 1.0 m3/hr holding tank, 28-man cap, Marpol compliance-1000, 1.0 m3/hr @ 25mH, <15ppm, IMO Resolution compliance

OTHERS

Reefer Points	: 4 x 32 amp. 415/3/50Hz
Welding Machine	: 4 x 16 Ampsm 240/1/50Hz : 1 set complete with 90 m length

