

MV JM SAMUDERA

Anchor Handling Tug Supply Vessel
70 M 10888 BHP 152 MT Bollard Pull DP2



PRINCIPAL PARTICULARS

Length Overall	: 70.0 m
Length W.L	: 68.40 m
Breadth Molded	: 16.00 m
Depth Molded	: 6.5 m
Draft Molded	: 5.80 m
Class	: Bureau Veritas
Flag/Port Registry	: Malaysian/Port Klang
Delivery	: 2011
Official No.	: 334348
IMO No.	: 9610511
Call Sign	: 9MLT9
Hull No.	: 20089
GRT/NRT	: 2348/704
Place of Built	: Muhibbah Marine Eng.

PERFORMANCE

Performance Speed	: Min 13 knots
Economical Speed	: Min 11 knots
Endurance	: Min 25 days

CARGO CAPACITIES

Deck Strength	: 5.5mt/m2
Cargo Deck Area	: 500 m2
Fuel Oil Tank	: 838.40 m3
Drill Water	: 625.90 m3
Fresh Water	: 419.80 m3
Foam Tank	: 14.80 m3
Liquid Mud / Brine Tank	: 324.30 m3
Base Oil Tank	: 216 m3
Cement Tank	: 2 x 2375 CUF and 2 x 1750 CUF

DISCHARGE RATE

Fuel Oil Cargo Pump	: 2 x 100 m3/Hr @ 90m head
Fresh Water Cargo Pump	: 1 x 100 m3/Hr @ 90m head
Drill Water Cargo Pump	: 1 x 100 m3/Hr @ 90m head
Liquid Mud/Brine Pump	: 2 x 100 m3/Hr @ 90m head
Brine Cargo Pump	: 1 x 100 m3/Hr @ 90m head
Base Oil Cargo Pump	: 1 x 100 m3/Hr @ 90m head

PROPULSION SYSTEM

Main Engines	: 2 x 5444 BHP (10,888 BHP) Caterpillar C28012
Bow Thruster	: 1 x 10T Motor Driven CPP Tunnel Thrusters 3 x 12T Retractable Azimuth Thrusters, Engine Driven
Stern Thrusters	: 1 x 10T Motor Driven CPP Tunnel Thrusters
Propellers	: 2 x CPP
Shaft Alternator	: 2 x 1250 kW, 415/3 phase/50Hz Stamford
Auxiliary Generator	: 2 x 450 kW, 415/3 phase/50Hz CAT C18
Emergency Generator	: 1 x 82 kW, 415/3 phase/50Hz CAT 4.4

TOWING / ANCHOR HANDLING EQUIPMENT

Bollard Pull	: Average 152 MT, Max 158 MT
Towing Winch	: Twin drums in waterfall configuration, Brake holding: 450 Ton @ 1st layer, Braastaag Tom Drum Wire
Stern Roller	: 2.0 m dia x 5.0 m length, 450 SWL
Karm Fork	: 1 set Karmoy Ref: M330120 SWL 300 tone
Towing Pins	: SWL 160 MT
Storage Reel	: 1 x 5 tons @ C-20m/min

DECK EQUIPMENT

Capstan	: 2 x 10T @ 25 m/min
Tugger Winch	: 2 x 16.90T @ 27.50 m/min
Anchor Windlass	: 11.9T @ 13.80 m/min max duty, 45mm chain

ACCOMMODATIONS

Crew + Passengers	: 2 x 1 berth cabins 4 x 2 berth cabins 8 x 4 berth cabins Total 42 berth
-------------------	--

All cabin fully air-conditioned

Walk-in Freezer space	: 10.0 m3
Walk-in Chiller	: 12.0 m3

RADIO & NAVIGATION EQUIPMENTS

SSB (additional)	: 1 x Furuno FS-1570 150W MF/HF
VHF	: 2 x JRC-7705
Radar	: JRC, JMA-5312-6, X-Band with ATA, 95mm range
Echo Sounder	: 1 x JRC, IFE-680, @-800m
Gyro Compass	: 3 x C, Plath Navigat
GMDSS	: For Sea-Area A1+A2+A3 operation JRC-296, 250W MF/HF
Magnetic Compass	: 1 x Lilley & Gillie MK2000
Speed Log	: 1 x JRC, JLN-205
Auto Pilot	: 1 x Navitron PID, NTR88G
Navtex Receiver	: JRC, NCR-333
GPS Navigator	: 1 x JRC, NWZ-4570
Joystick	:
EPIRB	: 1 set GME 406/121.5MHz
AIS	: 1 x JRC, JHS-182
Fleet Broadband	: 1 set Thrane & Thrane FBB 250

LIFE SAVING & H.S.E. EQUIPMENTS

Search Lights	: 2 x 2000W
Floodlights	: Fitted
Life Jackets	: 51
Liferafts	: 4 x 25 men & 2 x 15 men
Lifebuoys	: 10 sets
Firemen Suits	: 6
Scrambling Net	: 2 pcs
Rescue Boat	: 1 x 6 men, 25HP Outboard Motor
Slewing Davit	: As per SOLAS requirement

FIRE FIGHTING EQUIPMENT [FIFI Class I]

External

Fire Pump	: 2 x 1500 m3/hr at 1.4 Mpa each
Fire Monitor	: 2 monitors (water & foam, manual and remote control)

Oil Dispersant Boom : 1 set

Internal

CO2 system in engine room	: Fitted
---------------------------	----------

OTHERS

Reefer points	: 4 x 22 amp 415/3/50Hz 4 x 16 amp 240V/1/50Hz
---------------	---

FOR CHARTER INQUIRIES

Tel : +609 8511 1100

Fax : +609 858 9258

Email : commercial@jasamerin.com.my

www.jasamerin.com.my

JM SAMUDERA GENERAL ARRANGEMENT PLAN

